

Slotted Shims



Standard 302/304 SS A, B, C & D Shims

Slotted Leveling Shims are used for shaft alignment of rotating equipment. The power source (motor/ engine) shaft must be aligned with the mating equipment shaft (pump, compressor, gearbox, etc). Without proper alignment, equipment may experience damaging vibration or excessive shaft and bearing wear all resulting in mechanical breakdown.

Size	Slot Depth	Slot Size	Width	Length
A	1-9/32"	5/8"	2"	2-17/32"
B	2-1/8"	7/8"	3"	3-5/8"
C	2-3/4"	1-1/4"	4"	4-3/4"
D	3-5/8"	1-5/8"	5"	6"
E	4"	2"	6"	6"
H	6"	2-3/8"	8"	8"

E & H shims are only available in the following thicknesses: .001, .002, .003, .004, .005, .010, .015, .020, .025, .050, .075, .100 & .125

Thickness	Deluxe Kit	Full Kit	Tool Crib Kit	Maintenance Kit	Service Assort.	Installer Assort.	Replacement Packs
.001"	20ea	20ea	10ea	20ea	10ea	∅	20pc
.002"	20ea	20ea	10ea	20ea	∅	∅	20pc
.003"	20ea	20ea	10ea	20ea	10ea	∅	20pc
.004"	20ea	20ea	10ea	20ea	∅	∅	20pc
.005"	20ea	20ea	10ea	20ea	10ea	∅	20pc
.006"	20ea	∅	∅	∅	∅	∅	20pc
.007"	20ea	∅	∅	∅	∅	∅	20pc
.008"	20ea	∅	∅	∅	∅	∅	20pc
.009"	20ea	∅	∅	∅	∅	∅	20pc
.010"	20ea	20ea	10ea	20ea	10ea	∅	20pc
.012"	20ea	∅	∅	∅	∅	∅	20pc
.015"	20ea	20ea	10ea	10ea	10ea	∅	20pc
.020"	20ea	20ea	10ea	10ea	10ea	∅	20pc
.025"	20ea	20ea	10ea	10ea	10ea	∅	20pc
.031"	20ea	∅	∅	∅	∅	∅	20pc
.050"	8ea	20ea	10ea	4ea	10ea	12ea	10pc
.062"	8ea	∅	∅	∅	∅	∅	10pc
.075"	8ea	20ea	10ea	4ea	∅	12ea	10pc
.100"	8ea	20ea	10ea	4ea	∅	12ea	5pc
.125"	8ea	20ea	10ea	4ea	∅	12ea	5pc
Total PC.	340 PC.	260 PC	130 PC	166 PC.	80 PC.	48 PC.	